

PetBuckle™ Seat Belt Harness and Travel Kit

[Seat Belt Harness sold separately or with Travel Kit]

Kit contains:



SEAT BELT HARNESS



KWIK-CONNECT TETHER



SEAT BELT ADAPTER



STORAGE BAG


How to put the PetBuckle Seat Belt harness on your dog




(1) Unfasten all buckles on harness. Place loop over dog's head, bringing the loose straps under the dogs legs and resting the buckles and metal rings on dogs back.



(2) Adjust the triangle web guide to the lower portion of the dog's chest, allowing the straps to crisscross. The straps must crisscross to hold your pet in a sudden stop.



(3) Insert the adjustable tongue into the buckle on each side of the harness.



(4) Tighten the harness by pulling on the free-end of the straps. Note: to loosen harness push the adjuster towards the tongue to create slack.


To remove the harness, push the red release buttons on the buckles and lift harness off the dog.

The right attachment for your car.

For best safety results, follow the recommended attachments based on the weight of your dog.

Weight	Latch Bar	Seat Belt Adapter	Harness Loop
10-60 lbs.	X	X	X
10-120 lbs.		X	X
10-200 lbs.			X


[The harness loop provides the strongest securement.]



Option 1-Latch Equipped Vehicle.

(Latch equipped vehicles have at least two sets of small bars, called anchors, located in the back seat where the cushions meet. Latch is required on vehicles manufactured after September 1, 2002. See vehicle owner's manual for additional information.)

Latch option is only for dogs from 10 to 60 pounds. Using the Kwik-Connect Tether, attach the snap hook to the metal ring of the harness and the connector onto the anchors. Listen for a click as the connector latches to the anchor and pull to make sure the connector is locked in place. For added safety, it is recommended that the tether be adjusted to the shortest length comfortable for the dog.



Option 2-Seat Belt Adapter

Seat Belt Adapter is for dogs 10 to 120 pounds. Slip seat belt through the Seat Belt Adapter loop and buckle the seat belt. The Kwik-Connect Tether can now be attached to the metal ring on the adapter.



Option 3-Use Vehicle Seat Belt


Seat belt can be used for dogs 10 to 200 pounds. Slip the vehicle's seat belt through the loop of the harness on the dogs back and buckle the seat belt.

FOR STANDARD SIZE HARNESS AND STANDARD SIZE TRAVEL KIT ONLY

The PetBuckle® Standard Harness and Standard Travel Kit will fit any dog with a minimum chest circumference of 14" (approximately 10-12 lbs.) all the way up to dogs weighing 200 lbs. Chest circumference is the distance measured around the chest just behind the front legs.

Custom-fitting the harness to your dog:

- 1) After harnessing your dog, snug the harness by pulling on the adjustable straps, making the excess equal on both sides. Cut excess, leaving approximately 8 inches seat belt webbing. This will allow for adjustment should the dog gain weight.
- 2) After cutting the seat belt web, singe the cut edge of the web by using a match or lighter. This will help prevent the seat belt web from unraveling.
- 3) Stow the excess web out of the way by threading the web back through the buckle as shown in the illustrations below.* If readjustment is needed, simply unthread the excess web.



*Insert end of 8" webbing through the front of the buckle as shown in figure 1. Pull webbing through and insert in the back as shown in figure 2. Make sure webbing is taut.

CAUTION:

FOR YOUR DOG'S SAFETY, WE RECOMMEND:

- Attaching the Kwik-Connect Tether to the PetBuckle® Seat Belt Harness, rather than to your dog's collar.
- If your harness or tether show signs of wear or cut web, replace harness at once.
- Do not leave your dog unattended on hot days. Temperatures in enclosed vehicles can rise to dangerous levels. Make sure your dog always has adequate ventilation.
- Do not attach a dog weighing more than 60lbs. to the latch bar! Doing so could damage the latch bar in a sudden stop. Use other attachment points if your dog weighs more than 60lbs.
- Straps must criss-cross at the triangle web guide. Harnesses used without criss-crossed straps will not hold in a sudden stop.
- For the greatest safety, adjust the tether to the shortest length comfortable for your dog.

WARNING:

Do not place a restrained pet in the front seat of a vehicle with a passenger air bag unless the air bag is turned off. DEATH or SERIOUS INJURY can occur. The back seat is the safest place for your pet.

IMMI provides a limited warranty, covering defects in workmanship and material for one year from date of purchase. THE DURATION OF ALL OTHER EXPRESS AND IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PURPOSE, IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. Since the application of this product is beyond IMMI's control, IMMI's liability, and the purchaser's sole remedy, relating to the installation, application, or use of this product shall be strictly limited to recovery of its purchase price, and shall under no circumstances include recovery any other direct, indirect, or consequential damages, whether based on damage to or loss of cargo, damage to vehicle, or any other damages.